

Part No **36302**

2M DISPLAYPORT 1.4 CABLE, CROMO LINE

DP MALE TO MALE



DESCRIPTION

Superior performance and design DisplayPort cable
 Supports UHD resolutions up to 8K 7680x4320@60Hz 4:2:2 8bit, including 4K 4096x2160@160Hz 4:4:4 8bit
 Chrome design ABS housing, 24K gold plated connectors and contacts
 Triple shielded cable, corrosion resistant, high performance tinned copper 28AWG conductors
 DisplayPort 1.4, 8K, 4K, 3D, 32.4Gbps; 10 year warranty

From the Lines cable connectivity concept developed by Lindy, Cromo Line DisplayPort cables are high performance, designer connections that combine premium construction materials with striking connector architecture.

Cromo Line DisplayPort Cables feature triple shielded construction with 28AWG conductors for premium performance and corrosion resistance. High quality 24K gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

UHD resolutions up to 8K 7680x4320@60Hz 4:2:2 8bit, including 4K 4096x2160@160Hz 8bit, are supported. Cromo Line DisplayPort cables are capable of delivering 4:4:4 colour spacing for the most accurate colour representation possible.

Cromo Line cables feature sleek chrome design ABS housing to complement the aesthetics of style focused commercial and home applications.

Cromo Line DisplayPort cables are available in lengths from 0.5m to 5m.

RELATED PRODUCTS

36300 - 0.5m [1.64ft]
 36301 - 1m [3.28ft]
 36302 - 2m [6.56ft]
 36303 - 3m [9.84ft]
 36304 - 5m [16.40ft]

2M DISPLAYPORT 1.4 CABLE, CROMO LINE

CONNECTORS

Connector A	DisplayPort Male
Connector B	DisplayPort Male
Housing Material	Chrome plated ABS
Connector Plating	24K Gold 3µm
Pin Construction	Phosphor Bronze
Pin Plating	24K Gold 15µm
Dimensions (approx.) WxDxH	19.7x38.9x12mm [0.77x1.53x0.47in]

CABLE CONSTRUCTION

Length	2m [6.56ft]
Standard	DisplayPort 1.4
Colour	Grey
Type	Round
Jacket Diameter	7.3mm [0.29in]
Jacket Material	PVC
Conductor Material	Tinned Copper
Conductor Gauge	28AWG
Shielding	Copper Braid 85%

SPECIFICATIONS

Supported Bandwidth	32.4Gbps
Maximum Resolution	7680x4320@60Hz 4:2:2 8bit 4096x2160@120Hz 4:4:4 8bit
Nominal Attenuation	300kHz-825MHz <5dB 825MHz-2.475GHz <5dB 2.475GHz-4.125GHz <12dB 4.125GHz-5.1GHz <20dB
Minimum Bend Radius	73mm [2.87in]
Operating Temperature	-20°C - 80°C [-4°F - 176°F]
Storage Temperature	-25°C - 85°C [-13°F - 185°F]
ATC Approved	-

MISCELLANEOUS

Packaging Type	Polybag
Warranty (Years)	10
Certified	RoHS, REACH, UL

PURCHASING INFORMATION

No.	36302
EAN	4002888363020

AVAILABLE IN OTHER LENGTHS

36300 - 0.5m [1.64ft]
36301 - 1m [3.28ft]
36302 - 2m [6.56ft]
36303 - 3m [9.84ft]
36304 - 5m [16.40ft]