

Part No. 42344

2 PORT DISPLAYPORT 1.2, USB 2.0 & AUDIO CABLE KVM SWITCH

SWITCH BETWEEN 2 DISPLAYPORT EQUIPPED PCS FROM ONE KEYBOARD, MOUSE AND MONITOR



DESCRIPTION

- Control two DisplayPort equipped PCs from a single keyboard, mouse and monitor
- Switch via the unit's push button control, software or keyboard hot keys
- Supports DisplayPort 1.2 signals, up to 4K 60Hz
- Integrated cables for quick, hassle-free installation
- 2 Year Warranty

The Lindy 2 Port DisplayPort 1.2, USB 2.0 & Audio KVM Switch is a compact solution for providing access and control over two DP equipped PCs from a single keyboard, mouse and monitor. With integrated cables, this switch can be easily connected directly to the system, with no need for purchasing additional cables and saving time on the installation.

Support for resolutions up to 4K Ultra HD 60Hz ensures the optimum image quality, perfect for high graphical content in gaming setups, video editing or dual system control workstations. The audio output port on the main unit also allow users to connect headphones or speaker to add immersive 2CH audio and a microphone, while additional USB peripherals can be integrated with a USB hub.

The KVM switch features multiple switching options including a push button control [with 1.5m cable], hotkey and software switching to provide simple, reliable control for the user, great for both professional and first time users.

Please note: Software control & hotkey switching are not currently compatible with devices supporting macOS 10.15. This is due to an incompatibility between macOS 10.15 and 32-bit software.

RELATED PRODUCTS

42341
42345
32811
32321

2 PORT DISPLAYPORT 1.2, USB 2.0 & AUDIO CABLE KVM SWITCH



SPECIFICATIONS

AV Interface	DisplayPort
Console Interfaces	USB
Interface Standard	DisplayPort 1.2, USB 2.0
Maximum Resolution	4096x2160@60Hz 4:4:4 8bit
HDCP Support	HDCP 1.4
Supported Audio	Analogue Stereo
Separate Audio Ports	2 x 3.5mm [Female]
Serial Interface	-
Console Number	1
Max Number PC/Server	2
Cascadable	-
Switching Method	Push Button, Hotkey Switching & Software
19" Rack Mountable	-
Special Features	Supports USB 2.0 Hubs And Device Sharing, Active LED Indicators

CONNECTORS

Console Interfaces	DisplayPort [Female], USB 2.0 Type A [Female], 2 x 3.5mm [Female]
PC/Server Interfaces	2 x DisplayPort [Male], USB 2.0 Type A [Male], 2 x 3.5mm [Male] 1.2m Integrated Cables
Other Interfaces	-

Power

MISCELLANEOUS

Packaging Type	Carton Box
Packaging Dimension	160x60x250mm (6.3x2.36x9.84in)
Gross Weight	0.514kg (1.13lb)
Warranty (Years)	2
Certificated	CE, FCC, RoHS, REACH & California Proposition 65

PHYSICAL PROPERTIES

Dimensions (approx.) WxDxH	97x25x82.18mm [3.82x0.98x3.24in]
Housing Material	Plastic
Net Weight	0.433kg (0.95lb)
Operating Temperature	0°C - 40°C (32°F - 104°F)
Storage Temperature	-20°C - 60°C (-4°F - 140°F)
Humidity	0 - 90% RH (non-condensing)
Power Requirements	5V
Colour	Black

PURCHASING INFORMATION

No.	42344
EAN	4002888423441

PACKAGING CONTENTS

DisplayPort KVM switch
Lindy Manual

DISCOVER **LINDY**
lindy.com